

MAN TGA 33.430 6x6 с кузовом 16 м3

001AA steering arrangement, left
005NW wheelbase 3900+1400 mm
006CI rear frame overhang 800 mm
018DD engine D2066LF01 - 430 hp / 316 kW
EURO3 - 2100 Nm Common Rail
02AAB instrument panel kmh 'Base-Line'
022GE gearbox ZF 16 S 252 OD
023CT fuel tank 300l right
025MS front axle VP-09 driven
026EE front springs parabolic 9.0 t
027AN radiator and intercooler for up to 35 degrees
ambient temperature
028ED rear springs trapezoidal 16 t
028PA Anbau Doppelachse
03KAA fuel tank fitted
030EE steering wheel with height and inclination adjustment
032AB MAN BrakeMatic (electronic brake system)
034EC brake shoe width for rear axle 220 mm
034MH hub-reduction rear axle HPD-1382/ HP-1352
035KL planetary axle ratio $i = 4.00$
037AC with differential lock in rear axle
037CA differential lock in front axle without buzzer
037CM restricted steering control when FA diff. lock is engaged
038GH disc wheels 10 hole 11.75-22.5 on 1st FA TL
038PG disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TG disc wheel 10-hole 9.00-22.5 as spare wheel TL
042DE digital tachograph
05NAE front panel unlockable from inside
050NN M cab 2240mm wide, 1880mm long
052XA without stowage boxes
058BA seat coverings in standard quality
058NH driver's seat, high-comfort, with air suspension
059NA co-driver's seat static, with longitudinal + seat back adjustment
080AE door interior panelling washable
116AE visco fan
118MA EDC engine regulation
122QH PTO NH/1C without flange $f=0.91/1.09$ right side, horizontal
123CC strainer for fuel tank
124AL fuel filter
124EA fuel filter heating
142AF calibrate tachograph
146AF front wheel drive (dis)engageable
146KA transfer case G172
153KC air conditioning system AC R134A with automatic temperature control without CFHC
159XS without cab insulation NORDIC (against cold) for M, L and LX cab
194AD operator's manual in GERMAN
196AW sticker D20 COMMON-RAIL on front panel
201AS air intake raised with dry air filter
201FA fine dust and pollen filter
205AN air compressor 1-cylinder, 360 ccm
206ET exhaust on lh side with tail pipe towards rear
208AK exhaust valve brake
210AA flame starting system
211FF single-plate clutch MFZ 430
227AA front axle breather upswept
227AC rear axle breather upswept
230AH rear underride guard, round
230XW without front underride guard

230YX without lateral underride guard
 233EM 3-part steel bumper
 234EZ trailer coupling RINGFEDER 2050 A for central-axle trailer
 236AF cross member for trailer coupling
 241AC without platform mounting brackets
 245AT spare-wheel holder on left-hand side inclined
 256AF steering wheel lock with immobiliser
 257XL standard steering wheel for 'M' cab
 258HA anti-lock braking system (ABS)
 259CC drum brake for front axle
 259CE drum brake for rear axle
 262AC brake connection 2-line
 263AF asbestos-free brake linings
 272FA entry lighting for driver and co-driver
 280EC fly mesh guard before radiator
 281AA high design
 283FB cab mounts on coil springs for 'M' cab
 284LE Important: poorer ride comfort due to trapezoidal rear springs
 303AA tank cap lockable - 1 cap w/o vent
 309AA beam throw regulator
 310EE halogen twin headlights H7 for right-hand traffic
 318AA marker lamps
 318AK lateral marker lights
 319AR reading lamp for driver
 321EC central locking
 324AC two-tone horn, electric
 325AA MAN Tronic (on-board computer)
 325EA Language 1 'German' for display in instrument panel
 325FC language 2 'English' for display in instrument panel
 326CK trailer socket for anti-skid system on frame end
 326CW trailer socket 24V 7+7-pole on frame end
 329CS batteries 12V 155Ah, 2 pcs
 329ER battery box up to 175Ah
 331CB alternator 28V 80A 2240 W
 337AH oil pressure gauge
 337AK oil temperature gauge
 339FA time in instrument panel (trip data)
 345AV speed limiter electronic 85 km/h
 345EA cruise control
 346CA charging pressure indicator
 350LK CB radio antenna on cab roof
 350NH radio MAN CC 24V
 351AF preparation for radiotelephone
 362AH stabilizer on both rear axles
 363AA stabilizer for front axle
 370CM air dryer
 373AD antifreeze down to -25 degrees
 376XH without mattress for lower bunk
 376XK without mattress for upper bunk
 376XL without bunk for 'M' and 'C' cab
 378XE without pillow
 380AA windscreen of laminated glass clear
 381AA cab rear wall without windows
 381XC without curtain before bunks
 381YA without all-round curtain for C/M cab
 385AR side windows behind B-post
 386AS mechanical sliding roof
 387AF electric door window lifters for driver and co-driver
 388AH roller blind for windscreen, mechanical
 388AK sun shade in front of windscreen
 389AC handles left and right (on B-post)
 389AD handles left and right (on A-post)
 390AT oddments box

390XN without waste paper bins between theseats
 392AH kerb mirror, right
 392AK rear-view mirror(s) heatable and electrically adjustable
 392AN wide-angle mirror on right, heatable
 392AU wide-angle mirror on left, heatable
 392HA mirror brackets for body width 2500-2600 mm width 2500 mm
 395AA ashtray on co-driver's side
 400AH mudflap front
 401CY synthetic mudguards, 3-part, with mud flaps
 404AP spray reducer
 405AC first-aid kit
 405AK hazard-warning sign
 405AR hazard-warning lamp
 407AH jack 12 t
 411AF 2 chocks
 434ES dashboard in standard version
 534FR permissible front axle load 9000 kg
 538AE plastic floor and engine tunnel covering
 542FB anti-noise package for 82 dB limit (92/97 EEC) all-wheel drive
 600AC Fittings for right-hand traffic
 LQW01 chassis in water-based paint
 LVS01 chassis graphite black RAL 9011 matt
 LVS02 wheels White aluminium acrylic RAL 9006
 LVS03 cab Pure white RAL 9010
 80001 2 Dunlop 385/65R22,5 SP 362 TL 160
 90001 4 wahlweise 315/80R22,5 ANTR-S+G TL
 90002 4 wahlweise 315/80R22,5 ANTR-S+G TL
 90004 1 wahlweise 315/80R22,5 LENK-S+G TL
 Gross weight: 33000
 1st front axle: 9000
 2nd front axle: 0
 3rd front axle: 0
 Leading axle: 0
 1st rear axle: 13000
 2nd rear axle: 13000
 Trailing axle: 0